

PRODUCT INFORMATION



Lubricants - Engine Oil - Motorcycle Motor Oils

Version: 318/02

DuraBlend™ 4T SAE 15W-50

High performance semi synthetic motor oil for four-stroke motorcycle engines.
Formulated to meet the requirements of all leading engine manufacturers.

Performance levels

| |
|----------|
| API: SL |
| JASO MA |
| JASO MA2 |

Applications

Four-stroke motorcycle engines where API SL or JASO MA or JASO MA2 fluids are required.

Optimized for lubrication systems where engine, gearbox and clutch are integrated (wet sump).

Suitable for high-performance motorcycles.

Features & Benefits

High performance

Durablend 4T engine oil is formulated with high quality base oils and additives to ensure maximum performance output for two wheel vehicles.

Wet clutch compatible

Optimal frictional characteristics for maximum power transfer, smooth shifting and proper protection of the wet clutch. (JASO MA approved).

Wear protection

Strong oil film and enhanced product stability provide long lasting engine protection.

Engine cleanliness

Keeps the engine clean by minimizing deposits.

Easy starts

Recommended for quick starting. Even under very cold conditions or after long periods of engine inactivity.

PRODUCT INFORMATION



Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvolineeurope.com

Typical properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

| DuraBlend 4T | |
|--|--------|
| SAE Viscosity Grade | 15W-50 |
| Viscosity, mm²/s @ 100 °C. ASTM D-445 | 18,6 |
| Viscosity, mm²/s @ 40 °C. ASTM D-445 | 141 |
| Viscosity Index ASTM D-2270 | 148 |
| TBN, mg KOH/g ASTM D-2896 | 6 |
| Pour Point, °C ASTM D-5949 | -33 |
| Specific Gravity @ 15.6°C. ASTM D-4052 | 0,892 |
| Flash Point, COC, °C. ASTM D-92 | 236 |

**This information only applies to products manufactured in the following location(s):
Europe**

™ Trademark of Valvoline, registered in various countries © 2016

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.

Health & Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet <http://msds.valvoline.com>

Protect the environment

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

Storage

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces – 318/01