



QUALIFIER FORK OIL

Description

Synthetic hydraulic oil for motorcycle forks and shock absorbers. It has exceptional shearing resistance and is suitable for sports and urban use. It has excellent antioxidant, anticorrosion and antiwear properties. It releases the air bubbles produced in shock absorber systems by maintaining homogeneous and smooth behaviour at all times within a wide range of temperatures.

Properties

- Good performance when faced with changes in temperature due to its high viscosity index.
- Good shock absorbing characteristics and compatibility with oil seals.
- Excellent anti-friction performance thanks to its special additives.
- Great resistance to ageing and good anti-rusting and anticorrosive properties.

Quality levels, approvals and recommendations

- DIN: 51524 Part 3 HVLP (10W, 5W)

Technical specifications

	UNIT	METHOD	VALUE		
SAE Grade			5W	10W	15W
Density at 15 °C	g/cm ³	ASTM D4052	0.836	0.846	0.842
Kinematic viscosity at 100 °C	cSt	ASTM D445	4.9	8.3	10.8
Kinematic viscosity at 40 °C	cSt	ASTM D445	22	46	64
Viscosity index	-	ASTM D2270	150	157	160
Flash point, open cup	°C	ASTM D92	200	232	250
Pour point	°C	ASTM D97	-54	-40	-36

The above mentioned characteristics are typical values and should not be considered product specifications.