

## Description

Lubricant oil for general use in 2-stroke engines. It is suitable for a wide range of motorcycles and is mainly recommended for urban use. It is a clean oil, which cares for the engine and always keeps the exhaust vents clean. In addition, it supports very high temperatures produced by intensive use in city traffic, or as a consequence of carrying a passenger on a scooter or a small cylinder capacity motorcycle.

## Properties

- Increased lubricating power that reduces wear, extending the engine's life span.
- Minimizes the formation of deposits, keeping the exhaust ports clean.
- Reduces spark plug sweating and prevents the piston rings from sticking.
- Also suitable for lawnmowers, chainsaws and other equipment used for DIY or small-scale agriculture.

## Quality levels, approvals and recommendations

- JASO M345 FB
- API TC
- ISO-L-EGB

## Technical specifications

	UNIT	METHOD	VALUE
Density at 15 °C	g/cm <sup>3</sup>	ASTM D 4052	0,880
Viscosity at 100 °C	cSt	ASTM D 445	8,9
Viscosity at -40 °C	cSt	ASTM D 445	65
Viscosity index	-	ASTM D 2270	110
Flash point, open cup	°C	ASTM D 92	146
Pour point	°C	ASTM D 97	-15
T. B. N.	mg KOH/g	ASTM D 2896	1,6
Sulphated ashes	% weight	ASTM D 874	0,1

The above mentioned characteristics are typical values and should not be considered product specifications.