

# TECHNICAL DATA SHEET

## HOUGHTON A 4120 NON FERROUS ROLLING ADDITIVE

Houghton A 4120 boosts corrosion resistance in an Non Ferrous rolling emulsion.

### Applications

Houghton A 4120 is designed to work as metal deactivator and improves corrosion resistivity of metals.

### Recommendation for use

Houghton A 4120 is used (in case of corrosion issues) as an additive for the rolling emulsions in an Non Ferrous rolling application at concentration of 0,025%.

### Benefits

- To be used in case of corrosion issues in an Non Ferrous application.
- Compatible with the mechanical parts of the rolling mill.
- Compatible with waste treatment processes.

### Health, Safety and Handling

Please consult the Safety Data Sheet (SDS) for information on storage, safe handling and disposal. The conditions or methods of handling, storage, use and disposal of the product are beyond our reasonable control - we assume no liability for any ineffectiveness of the product or any injury or damage, arising out of or in connection with these conditions.

### Typical Physical Properties

PROPERTY	TYPICAL VALUE	UNIT
Appearance	Clear Brown Liquid	
Flash Point (FOC)	>60	[°C]
Density	1,035	[g/cm <sup>3</sup> @ 20°C]

All reasonable care has been taken to ensure this publication is accurate upon issue. Such information may be affected by changes subsequent to issue. This Technical Data Sheet is to be used solely for this product. Prior to any use, consult the Safety Data Sheet (SDS) for information on hazard risks and product use parameters. All liability and all warranties express or implied are hereby excluded as to product performance results, the accuracy of these data including any warranty of merchantability or fitness for any purpose. 61412000

