

ULTRACUT® 370 Plus

General purpose, semi-synthetic cutting and grinding fluid

Product Overview

ROCOL® ULTRACUT 370 Plus is a high dilution, semi-synthetic, general purpose, water mix cutting and grinding fluid formulated to give a long and predictable sump life with inherent resistance to degradation.

ULTRACUT 370 Plus is formulated to provide optimum performance at high dilutions on a wide range of ferrous and non-ferrous metals.

The versatility of ULTRACUT 370 Plus enables the user to rationalise to one fluid for both cutting and grinding operations.

ULTRACUT 370 Plus forms a translucent green micro-emulsion when mixed with water which provides a clear view of the workpiece.

Features and Benefits

- ULTRACUT 370 Plus is a multipurpose cutting and grinding fluid.
- Compatible with both hard and soft water.
- High dilutions providing low in sump costs.
- ULTRACUT 370 Plus is suitable for use with most materials.
- Excellent residual corrosion protection.
- Inherently resistant to degradation.
- Tolerant to tramp oil.
- Low foaming.
- Pleasant and safe to use.

Directions for Storage and Use

- ULTRACUT 370 Plus should be used between 40:1 and 60:1 for cutting and between 50:1 and 70:1 for grinding depending on the severity of operation, workpiece material and water hardness.
- To ensure dilution accuracy, it is preferable to use a ROCOL Automatic Fluid Mixer. For manual mixing, add the concentrate to the water at the recommended dilution ratio, stirring continuously.
- It is advisable to use the appropriate ROCOL ULTRAGUARD® Machine Tool Care product at fluid changeovers. Optimum fluid life is obtained by adequate initial machine cleaning, correct dilution control and regular maintenance of the fluid, particularly prior to weekends and shutdown periods.
- ULTRACUT 370 Plus should be stored in a cool, well ventilated area, between +5°C and +30°C, in the original container.
- If stored in accordance with the above guidelines, shelf life is 1 year from date of manufacture.

Typical Applications

- Multipurpose cutting and grinding operations on ferrous and non-ferrous metals.

Pack Sizes

Pack Size	Part Code
5L	51376
20L	51373
55L	51370
200L	51379

ULTRACUT® 370 Plus

General purpose, semi-synthetic cutting and grinding fluid

Property	Test Method	Result
Appearance:		
Concentrate	N/A	Green liquid
Mixed with water	N/A	Translucent green emulsion
Odour	N/A	Mild
pH	N/A	9.5 at 15:1 dilution
Density at 20°C (g/cm³)	N/A	1.00

Refractometer Calibration:

Dilution Ratio		30:1	40:1	50:1	60:1	70:1	80:1
Refractometer Reading		2.1	1.6	1.3	1.1	0.9	0.8

Values quoted above are typical and do not constitute a specification.

Safety Data Sheets

Safety data sheets are available for download from our website www.rocol.com or may be obtained from your usual ROCOL contact.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

Issue: 1 Date: 09-13

T +44 (0) 113 232 2600
 F +44 (0) 113 232 2740
 E customer-service@rocol.com
www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67
 Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



FM 12448



EMS 67596



OHS 78173

